The patented QT Connector secures airtight connection to tire valves. Easy to use as a quick connect coupling. Sold seperately or with JWL Inflating Gun.





150123-134





)

150111



150112



WV



Working pressure

Technical description

Gauge Precision 0-12 bar

Measurement

Connection

1/4" internal thread Max. 12 bar (174 psi) 0-12 bar (0-174 psi) +/-0.19 bar bar og psi



The inflating guns are mounted with a quality gauge (0-12 bar). It

is in accuracy class 1.6 in accordance with EN 837-1 standard.

All inflating guns are precision tested during production where

Inflating nipples are also sold seperately. The inflating nipples are connected directly to a compressed air coupling or hose.

the gauges have an accuracy of 0-12 bar: ±0.19 bar.

CAUTION: Always remember to check the tire pressure.

Inflating Guns

JWL Inflating Guns are used to inflate all types of auto tires. The functional and reliable inflating guns have infinite adjustment of the air volume. Moreover, air pressure is used to facilitate the activation of the handle. All JWL Inflating Guns are supplied with an air-escape valve on the side. Choose between inflating gun with QT Connector, twin-connector or clamping nipple.

The hose is available in different lengths, which gives the possibility of more mobility.

116021



The QT Connector can be delivered seperately and comes for hose connection or threaded.

The QT Connector is easy to use. Just push the connector on to the valve. The QT Connector is completely airtight when connected. Pull back to release it from the valve.



Art Ne

Art.No.

JWL Inflating Gun with QT Connector



Н		AILINU.
	Inflating Gun, ø63 mm pressure gauge, QT Connector, 0.5 m hose	151120-134
	Inflating Gun, ø63 mm pressure gauge, QT Connector, 1.0 m hose	
	Inflating Gun, ø63 mm pressure gauge, QT Connector, 1.5 m hose	
	Inflating Gun, ø80 mm pressure gauge, QT Connector, 0.5 m hose	
1	Inflating Gun, ø80 mm pressure gauge, QT Connector, 1.0 m hose	151134-134
	Inflating Gun, ø80 mm pressure gauge, QT Connector, 1.5 m hose	

JWL Inflating Gun with clamping nipple
Inflating Gun. ø63 mm pressure gauge, clamping nipp

Inflating Gun, ø63 mm pressure gauge, clamping nipple, 0.5 m hose	150120-134
Inflating Gun, ø63 mm pressure gauge, clamping nipple, 1.0 m hose	150126-134
Inflating Gun, ø63 mm pressure gauge, clamping nipple, 1.5 m hose	150122-134
Inflating Gun, ø80 mm pressure gauge, clamping nipple, 0.5 m hose	150130-134
Inflating Gun, ø80 mm pressure gauge, clamping nipple, 1.0 m hose	150134-134
Inflating Gun, ø80 mm pressure gauge, clamping nipple, 1.5 m hose	150138-134

JWL Inflating Gur	n with twin connector	
	Inflating Gun, ø63 mm pressure gauge, twin connector, 0.5 m hose	150123-134
	Inflating Gun, ø80 mm pressure gauge, twin connector, 0.5 m hose	150131-134

Inflation nipples	Art. No.		Art. No.
QT Connector 3/16" (ø5.5 mm) hose connection	116021	Coupler plug 1/4" hose connection, bicycle	150113
QT Connector 1/4" (ø6.5 mm) hose connection	116022	Coupler plug JWL 521 "Fr/N", car	150114
QT Connector internal thread 1/4" BSP	116002	Coupler plug JWL 521 "Fr/N", bicycle	150115
QT Connector internal thread 1/4" NPT	116032	Coupler plug JWL 522 "ORION", car	150116
Coupler plug JWL 520 "Euro", car	150110	Coupler plug JWL 522 "ORION", bicycle	150117
Coupler plug JWL 520 "Euro", bicycle	150111	Bicycle plug for mounting in clamping nipple	150118
Coupler plug 1/4" hose connection, car	150112		

